PP-S-01 SAFE PAGE / PARTY HANDSET

CCCC ZIZTEL

DS-020 Issue 04

Thank you for your interest in Ziztel – we are a UK based manufacturer of PAGA and Intercom Products. Our products are mainly designed for use in the Hazardous Oil, Gas and Petrochemical industries.

PP-S-01 allows open party line communications (providing group conference full duplex) as well as public address paging. The Ziztel page / party solution also includes the possibility of point to point selective communications enabling multiple private conversations.

See also PPX-16 page / party switch DS024.



PP-S-01 PAGE / PARTY HANDSET

Ergonomic construction – desk or wall safe area mounting

Supports standard full duplex telephone point to point communication – *selective multi speech path*

Corrosion proof plastic enclosure – *long through life*service

Mission critical communications – possible PAGA integration

The Ziztel safe area Page / Party Handset PP-S-01 is a telephone assembly designed to allow reliable two way voice communication *and* public address paging via a host loudspeaker system. The PP-S-01 is ergonomically styled to fit into a modern control room, office, laboratory or work shop environment and can be desk or wall / bulkhead mounted as required.

The PP-S-01 comprises of a key pad (enabling possible conventional PBX style operation), handset fitted with a retractable cord and a *push to page* button. The unit is designed to operate with ZEST PPX-16 page party handset subscriber switch which enables up to sixteen stations to be connected. An open 'group' channel supports party communications and the momentary push to page button enables immediate access to the site public address or PAGA loudspeakers.

The unit is delivered with a locking plug / socket which allows simple and rapid installation.

Technical Specification	
Connection	2 x twisted pair with overall shield min CSA / conductor is 0.75mm ²
Operating Voltage	Phantom powered from host amplifier, no local power required
Line Current	20mA
Page / Party button action	Momentary – push to initiate paging broadcast
PABX connection	2 wire analogue subscriber
Location	Safe Area / Internal
Temperature / Humidity	-10°C to + 70°C / 70% non-condensing
Colour	Charcoal Grey
Material	High impact plastic
Dimensions	300 x 250 x 70mm
Weight	0.5kg
Connection lead	1.5M with integral jack plug

^{*}Also available with noise canceling insert



PP-S-01 fitted inside an AH23 acoustic hood