

SPC6FT

6 WATT CEILING LOUDSPEAKER

DS-219 Issue 01



Thank you for your interest in Ziztel - we are a UK based manufacturer of PAGA and Intercom products. Our systems are mainly designed for use in the Hazardous Oil, Gas and Petrochemical industries.

Our products are very robust and designed to comply with international standards. The SPC6FT is a safe area loudspeaker designed to deliver intelligible public address speech and alarm tone signals in internal locations.

Please do not hesitate to contact us for further information on our products we look forward to working with you on a project

SPC6FT 6 WATT CEILING LOUDSPEAKER

Metal alloy construction – very robust

Integral transformer – range of power settings 1.5Watts to 6Watts

High sensitivity – efficient broadcast of voice frequencies

The SPC6FT is a public address ceiling loudspeaker designed for 100V line operation. The unit is equipped with integral line coupling transformer enabling power settings from 1.5Watts to 6Watts.

The unit is supplied with a protective rear dome which enables the integrity of false ceilings to be maintained. An aesthetically pleasing fascia grill allows discreet placement in cosmetically critical locations, use in less sensitive situations is readily accepted – example control rooms, cabins, offices, corridors. Field cable termination is made internally by removing the rear dome cover, single or dual penetrations can be cut to allow cable loop in/out.



ZIZTEL LIMITED

email: sales@ziztel.com web: www.ziztel.com tel: +44 (0) 115 9202888
mail: 96 Rolleston Drive, Arnold, Nottingham, NG5 7JP United Kingdom

All text, drawings and photography contained within this data sheet are the property of Ziztel Ltd and are subject to copyright. Information may neither be transmitted or copied to third parties without the express written consent of Ziztel Ltd. Ziztel Ltd have a policy of continuous product improvement and contents here in are liable to change without notice.

Technical Specification	
Material / Colour / Weight	Aluminium / RAL9010 / 0.7kg
Mounting / dimensions	Ceiling flush fit. Ceiling cut-out 160mm diameter / Overall dimensions 180mm x 100mm
Input voltage / Termination	100V / line integral terminal block
Location	Internal sheltered area
Maximum/minimum ambient temperature	+90 C / - 20 Centigrade
Rated/maximum power	6 Watts
Power tappings	6Watt, 3Watt, 1.5Watt
Voice coil	1.5 inch
Magnet size	80mm (D) x 15mm (H)
Overall dimensions	290mm (W) x 293mm (D) x 213mm (H)
SPL 1W/1m	8dBA, rated power 97dBA
Effective frequency range	100Hz – 13kHz (-20dB)

ZIZTEL LIMITED

email: sales@ziztel.com web: www.ziztel.com tel: +44 (0) 115 9202888
mail: 96 Rolleston Drive, Arnold, Nottingham, NG5 7JP United Kingdom

All text, drawings and photography contained within this data sheet are the property of Ziztel Ltd and are subject to copyright. Information may neither be transmitted or copied to third parties without the express written consent of Ziztel Ltd. Ziztel Ltd have a policy of continuous product improvement and contents here in are liable to change without notice.