

SAFE6T

6 WATT CABINET LOUDSPEAKER

DS-306 Issue 01



Thank you for your interest in Ziztel - we are a UK based manufacturer of PAGA and Intercom products.

Our systems are mainly designed for use in the Marine, Hazardous Oil, Gas and Petrochemical industries.

Our products are robust and designed to comply with international standards.

The Ziztel SAFE6T loudspeaker is specifically designed for use in MBS / PAGA / General alarm broadcast system applications and features high grade metallic construction with integral line transformer and wide range direct radiator.

ZIZTEL SAFE6T 6 WATT CABINET SPEAKER

All metallic construction – will not support combustion

Designed for Voice alarm VA / PAGA applications – excellent speech intelligibility

The Ziztel SAFE6T is a steel cabinet wall mount 100V line, 6 Watt rated loudspeaker designed for use in safety critical voice alarm / PAGA / MBS (Main Broadcast) system applications. The unit is part of the Ziztel range of loudspeaker devices which includes industrial ceiling flush fit, corridor 'bi directional' and horn loaded loudspeakers.

Safe6T provides reliable service in safe area internal locations.



ZIZTEL LIMITED

email: sales@ziztel.com web: www.ziztel.com tel: +44 (0) 115 9202888
mail: 96 Rolleston Drive, Arnold, Nottingham, NG5 7JP United Kingdom

All text, drawings and photography contained within this data sheet are the property of Ziztel Ltd and are subject to copyright. Information may neither be transmitted or copied to third parties without the express written consent of Ziztel Ltd. Ziztel Ltd have a policy of continuous product improvement and contents here in are liable to change without notice.

Technical Specification

Material / Colour	Steel / White RAL 9010
Mounting	Four bolts
Termination	Up to 2.5 mm cross sectional area solid conductors
Gland entry	2 x 20mm via 'knock outs'
Weight w/transformer	1,2 kg
IP-rating	30
Max. / min. amb. temp	110°C / -20°C
Rated / max. power	6 W / (8 or 10 Watts options available)
SPL 1W/1m	90 dB
SPL rated power	96 dB
Effective freq. range	180 – 13000 Hz
Dispersion (-6dB) 1kHz / 4kHz	187° / 77°
Directivity factor, Q	1,9
Dimensions	170 mm x 170 mm x 60 mm
Integral line transformer	100 Volt line 6 Watt / 3 Watt tap selection
Location	Internal safe area



ZIZTEL LIMITED

email: sales@ziztel.com web: www.ziztel.com tel: +44 (0) 115 9202888
 mail: 96 Rolleston Drive, Arnold, Nottingham, NG5 7JP United Kingdom

All text, drawings and photography contained within this data sheet are the property of Ziztel Ltd and are subject to copyright. Information may neither be transmitted or copied to third parties without the express written consent of Ziztel Ltd. Ziztel Ltd have a policy of continuous product improvement and contents here in are liable to change without notice.